

# AsteRx RB3 Pro

Rugged GNSS positioning receiver



Construction



Logistics & Port Operations



Mining



Automation

## Reliable positioning in harsh environments

Ultra-rugged housing combined with multi-frequency tracking and GNSS+ algorithms make AsteRx RB3 Pro the ideal GNSS receiver for applications that require accurate position in chemically aggressive environments, harsh temperatures and high mechanical stress.

## Ease of integration

The AsteRx RB3 Pro integrates seamlessly into any system thanks to fully documented interfaces, commands and data messages. Septentrio's open interfaces and software tools (WebUI, RxTools) make it easy to integrate, configure and control the AsteRx RB3 Pro receiver.

## Heading option

With optional dual-antenna input, AsteRx RB3 Pro provides precise, reliable and position independent heading combined with centimeter-level RTK. GNSS heading provides unmatched performance in both static and dynamic conditions removing the reliance on vehicle dynamics or magnetic sensors.

**AsteRx RB3 Pro high-accuracy GNSS receiver is designed to withstand the harshest of working environments in terms of temperature, corrosion as well as shock and vibration. For machine control applications it offers flexibility of installation and excellent GNSS performance.**

## KEY FEATURES

- ▶ **Rugged and durable IP69K housing**
- ▶ **High-accuracy RTK positioning with all-in-view, GNSS multi-frequency satellite tracking**
- ▶ **Sub-degree GNSS heading option**
- ▶ **GNSS+ algorithms ensure reliable performance in difficult environments**

## FEATURES

### GNSS signals

544 Hardware channels for simultaneous tracking of most visible signals:

- ▶ GPS: L1 C/A, L1C, L2C, L2 P(Y), L5
- ▶ GLONASS: L1 C/A, L2C/A, L3, L2P
- ▶ BeiDou: B1I, B1C, B2a, B2b, B2I, B3I
- ▶ Galileo: E1, E5a, E5b
- ▶ QZSS: L1 C/A, L1 C/B, L2C, L5
- ▶ NavIC: L5
- ▶ SBAS: EGNOS, WAAS, GAGAN, MSAS, SDCM

### Septentrio's patented GNSS+ technologies

- ▶ **AIM+** industry leading anti-jamming, anti-spoofing interference monitoring & mitigation technology
- ▶ **APME+** a posteriori multipath estimator for code and phase multipath mitigation
- ▶ **LOCK+** superior tracking robustness under heavy mechanical shocks or vibrations
- ▶ **IONO+** advanced scintillation mitigation
- ▶ **RAIM+** (Receiver Autonomous Integrity Monitoring)

### Formats

Septentrio Binary Format (SBF), fully documented with sample parsing tools  
NMEA 0183, v3.01, v4.0  
RTCM v2.x, v3.x (MSM messages included)  
CMR v2.0 and CMR+ (CMR+ input only)

### Connectivity

2 x RS232  
USB full speed (device)  
CAN/CAN-FD  
Ethernet 10/100Mbps  
2 x Event markers  
xPPS out

## SUPPORTING COMPONENTS

Embedded Web UI with full control and monitoring functionality.

RxTools, a complete and intuitive GUI tool set for receiver control, monitoring, data analysis and conversion.

GNSS receiver communication SDK. Available for both Windows and Linux.

## PERFORMANCE

### RTK performance <sup>1,2,3</sup>

Horizontal accuracy	0.6 cm + 0.5 ppm
Vertical accuracy	1 cm + 1 ppm
Initialisation	7 s

### GNSS attitude accuracy <sup>1,2,8</sup>

Antenna separation	Heading	Pitch/Roll
1 m	0.15°	0.25°
5 m	0.03°	0.05°

### Position accuracy <sup>1,2</sup>

	Horizontal	Vertical
Standalone	1.2 m	1.9 m
SBAS	0.6 m	0.8 m
DGNSS	0.4 m	0.7 m

### Velocity accuracy <sup>1,2</sup>

0.03 m/s

### Maximum update rate

Position	10 Hz
Measurements	10 Hz

### Latency <sup>4</sup>

<10 ms

### Time precision

xPPS out <sup>5</sup>	5 ns
Event accuracy	< 20 ns

### Time to first fix

Cold start <sup>6</sup>	< 45 s
Warm start <sup>7</sup>	< 20 s
Re-acquisition	avg. 1 s

### Tracking performance (C/N0 threshold)

Tracking	20 dB-Hz
Acquisition	33 dB-Hz

## PHYSICAL AND ENVIRONMENTAL

### SWaP

Size	168 x 118 x 51 mm
Weight	850 g
Input voltage	9 to 32 VDC

### Power consumption

GPS/GLO L1/L2	1.1 W
All signals, all GNSS constellations	1.3 W
Maximum	2.5 W

### Connectors

Antenna	2 x TNC
IO interfaces	23-pin TE AmpSeal

### Antenna LNA power output on TNC

Output voltage	5 VDC
Maximum current	150 mA

### Environmental

Operating temperature:	-40°C to +70°C
Ingress protection: IP69K (ISO20653) with mated connectors	
Vibration:	ISO16750-3
Test VII — Commercial vehicle, sprung mass (vehicle body) RMS 57,9m/s <sup>2</sup>	
Test IX — Commercial vehicle, unsprung mass 150-300m/s <sup>2</sup>	
Shock:	ISO16750-3
Shock II — Test for devices on rigid points on the body and on the frame	

### Certification

RoHS, WEEE, CE, FCC



<sup>1</sup> Open sky conditions

<sup>2</sup> RMS level

<sup>3</sup> Baseline < 40 Km

<sup>4</sup> 99.9%

<sup>5</sup> Including software compensation of sawtooth effect

<sup>6</sup> No information available (no almanac, no approximate position)

<sup>7</sup> Ephemeris and approximate position known

<sup>8</sup> Optional feature

### EMEA

Greenhill Campus (HQ)  
Interleuvenlaan 15i  
3001 Leuven, **Belgium**

Espoo, **Finland**

### Americas

Suite 200  
23848 Hawthorne Blvd  
Torrance, CA 90505, **USA**

[septentrio.com/contact](https://septentrio.com/contact)

### Asia-Pacific

Shanghai, **China**  
Yokohama, **Japan**  
Seoul, **Korea**

[septentrio.com](https://septentrio.com)

